

## LED Moving Sign Power Supply

# SS-400MS-5 Single Output Series



www.seasonic.com



### Dimension:

L215 × W115 × H50 mm

### Features:

- Universal input
- Built-in Fan speed control
- with Active PFC function
- Protections: SCP/OVP/OPP/OTP
- LED indicator for power on
- Forced air cooling by ball bearing fan
- Super high efficiency  $\geq 82\%$
- Top 3 Japan capacity, High Reliability
- Double forward layout design

### Output Specifications:

Model	Output power	Min. Load	Max. Load	Total power	VR
SS-400MS-5	5V	0A	80A	400W	4.5~5.5V
SS-350MS-5	5V	0A	70A	350W	4.5~5.5V
SS-300MS-5	5V	0A	60A	300W	4.5~5.5V
SS-250MS-5	5V	0A	50A	250W	4.5~5.5V
SS-200MF-5	5V	0A	40A	200W	4.5~5.5V

### General Specifications:

- Input voltage range: 90~264 Vac
- Input frequency: 47~63 Hz
- Hold up times: 16 (ms)
- Efficiency:  $\geq 82\%$  Average
- Regulation:  $\pm 1\%$
- Operation Temperature:  $-20\sim+70^{\circ}\text{C}$
- Storage Temperature:  $-20\sim+85^{\circ}\text{C}$
- Minimum 120,000 Hrs at full load at  $25^{\circ}\text{C}$  ambient

**Safety:** CB, CUL, TUV, CCC, BSMI

**EMC:** CE, FCC,

Sea Sonic Electronics Co., Ltd.  
www.seasonic.com  
sales@seasonic.com.tw  
Tel: +886 2 2659 0338  
Fax: +886 2 2659 0530

Seasonic Electronics Inc.  
www.seasonicusa.com  
usa@seasonic.com  
Tel: +1 626 969 9966  
Fax: +1 626 969 9986

Sea Sonic Europe B.V.  
europe@seasonic.com  
Tel: +31 (0)10-2262131  
Fax: +31 (0)10-2519947

Specification may change without prior notice

